

V3 COLDCAB CABINET CAPACITY SCHEDULE

REVISED ON JULY 2021

Calculated at 24° Ambient with 70% Relative Humidity					Power Requirements per cabinet			
Description		Watts Per Ft	Evap Temp	Temp Range	4Ft 1.205m	6Ft 1.805m	8Ft 2.405m	12Ft 3.605m
Deli	CAKE DISPLAYS DELI'S SQUARE OR CURVED GLASS	110 watts	-2°	5° to 8°	0.65 Amp	1.1 Amp	1.28 Amp	2.00 Amp
Deli	DELI'S DISPLAYS SQUARE OR CURVED GLASS	110 watts	-6°	2° to 4°	0.65 Amp	1.1 Amp	1.28 Amp	2.00 Amp
Deli	MEAT DISPLAYS DELI'S SQUARE OR CURVED GLASS	110 watts	-8°	0° to 2°	0.65 Amp	1.1 Amp	1.28 Amp	2.00 Amp
Deli	FREEZER -10° DELI'S SQUARE OR CURVED GLASS	200 watts	-20°	-10° to -15°	4.80 Amp	7.35 Amp	8.70 Amp	12.8 Amp
Deli	LOW MEAT DISPLAY	160 watts	-10°	0° to 2°	0.56 Amp	0.99 Amp	1.10 Amp	1.80 Amp
Deli	COMBO DELI CAKE	220 watts	-2°	5° to 8°	0.43 Amp	0.80 Amp	1.00 Amp	1.40 Amp
Deli	COMBO DELI	220 watts	-6°	2° to 4°	0.43 Amp	0.80Amp	1.00 Amp	1.40 Amp
Deli	COMBO DELI MEAT	220 watts	-8°	0° to 2°	5.23 Amp	7.00 Amp	8.50 Amp	12.20 Amp
Streamline	FRUIT & VEG UPRIGHT STD & V-ADDED (SL-8)	470 watts	-4°	4° to 6°	N/A	1.20 Amp	1.60 Amp	2.50 Amp
Streamline	CAKE UPRIGHT STD & V-ADDED (SL-8)	470 watts	-4°	5° to 6°	N/A	1.00 Amp	2.00 Amp	3.00 Amp
Streamline	COLD MEATS UPRIGHT STD & V-ADDED (SL-8)	470 watts	-7°	0° to 2°	N/A	1.20 Amp	1.60 Amp	2.50 Amp
Streamline	MEAT UPRIGHT STD & V-ADDED (SL-8)	470 watts	-9.7°	0° to 2°	N/A	7.80 Amp	9.60 Amp	14.00 Amp
Streamline	DAIRY UPRIGHT STD & V-ADDED (SL-8)	470 watts	-7°	2° to 4°	N/A	1.20 Amp	1.60 Amp	2.50 Amp
Uprights	FRUIT & VEG UPRIGHT STD & V-ADDED (VA-11)	470 watts	-4°	4° to 6°	N/A	1.20 Amp	1.60 Amp	2.50 Amp
Uprights	CAKE UPRIGHT STD & V-ADDED (VA-11)	470 watts	-4°	5° to 6°	N/A	1.00 Amp	2.00 Amp	3.00 Amp
Uprights	COLD MEATS UPRIGHT STD & V-ADDED (VA-11)	470 watts	-7°	0° to 2°	N/A	1.20 Amp	1.60 Amp	2.50 Amp
Uprights	MEAT UPRIGHT STD & V-ADDED (VA-11)	470 watts	-9.7°	0° to 2°	N/A	7.80 Amp	9.60 Amp	14.00 Amp
Uprights	DAIRY UPRIGHT STD & V-ADDED (VA-11)	470 watts	-7°	2° to 4°	N/A	1.20 Amp	1.60 Amp	2.50 Amp
Uprights	MEAT MEDIUM HIGH OR MEDIUM LOW	370 watts	-9.7°	0° to 2°	N/A	7.35 Amp	9.07 Amp	13.10 Amp
Uprights	FREEZER GLASS DOOR (GDF)	575 watts	-30°	-18° to -20°	N/A	21.5 Amp	23.50 Amp	27.00 Amp
Islands	FREEZER JUMBO ISLAND	285 watts	-30°	-18° to -20°	Crown –End 6.5 Amp		17.0 Amp	24.0 Amp
Islands	FREEZER JUMBO ISLAND (ICE CREAM)	285 watts	-35°	-18° to -25°	Crown –End 6.5 Amp		17.0 Amp	24.0 Amp
Islands	FREEZER WIDE ISLAND	285 watts	-30°	-18° to -20°	Crown –End 5.3 Amp		8.25 Amp	11.8 Amp
Islands	FREEZER WIDE ISLAND (ICE CREAM)	285 watts	-35°	-18° to -25°	Crown –End 5.3 Amp		8.25 Amp	11.8 Amp

Notes:

V3 Coldcab does not manufacture a 6ft Jumbo/Wide Island; where capacity stipulated 6ft Jumbo please note this is for Crown-Ends. For Upright Corner Wedges, Capacities to be calculated from 4ft. For Deli Corner Wedges, Capacities to be calculated from 4ft. Lengths excluding Patch-ends, add 45mm per Patch-end.

PLEASE NOTE:

This schedule replaces all previously dated schedules.

This schedule may also be updated/ changed without notice as V3 Coldcab continuously strives to improve our range of products.